



10,000 psi



For use with Cyl. Type	Description	Order No.***	Valve Type	Valve No.	Valve Function	Control Switch††	Motor	Reservoir Usable (cu. in.)
Single-Acting	Base model 1 1/8 hp pump with 2 1/2 gal. reservoir, remote motor control & 3-way valve.	<b>PE552</b>	3-Way	9582	Advance Return**	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Single-Acting	PE552, except also has solenoid operated remote valve.	<b>PE552S</b>	3-Way	9579	Advance Hold Return	Remote Motor & Valve	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Single-Acting	PE552, except has "Auto Dump" valve.	<b>PE552A∞</b>	Auto/Dump	9610	Advance Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Single-Acting	1 1/8 hp pump with 2 1/2 gal. reservoir. Valve has "Posi-check" feature.	<b>PE553</b>	3-Way†	9520	Advance Hold Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	Base model 1 1/8 hp pump with 2 1/2 gal. res. and 4-way valve for double-acting systems.	<b>PE554</b>	4-Way†	9506	Advance Hold Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	Weather-resistant model 1 1/8 hp pump with 2 1/2 gal. res. and 4-way valve for double-acting systems.	<b>PE554W</b>	4-Way†	9506	Advance Hold Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	PE554, except has 9500 tandem center valve.	<b>PE554T</b>	4-Way	9500	Advance Hold Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	For use with single-acting Spring Seat, Stressing Jack or double-acting cylinder.	<b>PE554P</b>	4-Way	9500	Advance Hold Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	For use with single-acting or double-acting Power Seat, Stressing Jacks ONLY.	<b>PE554PT</b>	4-Way	9628	Advance Hold Sequenced Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	Pump suitable to run multiple spring return tools.	<b>PE554C</b>	4-Way	9511†††	Advance Hold Return	Remote Motor	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525
Double-Acting	Pump equipped with 3/4-way solenoid valve.	<b>PE554S</b>	3/4-Way	9592	Advance Hold Return**	Remote Motor & Valve	1 1/8 hp*, 110/115 VAC 50/60 Hz, Single Phase	525

\* Pumps available with 230 volt, 60/50 Hz motors. Specify voltage when ordering. See "Assemble to Order" pump options on pp 100-103.

\*\* Holds with motor shut off.

\*\*\* To order PE55 series pumps with CSA approval, add "-C" to the Order No.

† Valves have Posi-Check® feature.

†† All remotes are 10 ft. long except for PE552S which is 25 ft. long.

††† Valving allows alternate and independent operation of two different spring return tools. Valve holds pressure only while valve is in "A" or "B" port position with pump motor shut off.

∞ Not to be used for lifting applications.